

### Kerala State Drugs and Pharmaceuticals Ltd (A Govt. of Kerala Enterprise) KALAVOOR. ALAPPUZHA

Phone :0477-2258184 (Extn:207) ; Email :ksdprmqtn@gmail.com Web :ksdp.co.in

KSDP/PS/F-ST/2023-24/20000135/T-87

1-2-2024

### Notice inviting sealed tender for the supply of 20mm Grey Butyl Rubber Stoppers Sterilized (Ready to use) - 500000 Nos

Quotations are invited for the supply of undermentioned goods/ services as per the attached specifications on FOR destination basis at our factory site at Kalavoor, Alapuzha, Kerala state

SI No.	ITEM CODE & DESCRIPTION	UNIT	QUANTITY	EMD	TENDER FEES
1	40900001	Numbers	5,00,000 NOS	Rs. 3175	Rs.784
	20mm Grey Butyl Rubber				
	Stoppers(Sterile)ready for use				

Quotations should be submitted as per the Proforma given below on your letter head.

SI No.	Name of item	Make	Rate per unit (including	GST %	Offer validity	Remarks, if any
			freight, if any)			

#### Due Date/Time : 8-Feb-24 / 03.00 PM

Opening Date/Time: 9-Feb-24 / 03.00 PM

Separate demand drafts should be submitted for Tender fee & EMD in favour of Kerala State Drugs & Pharmaceuticals Ltd payable at Alappuzha, Kerala.

Offer validity\*: Minimum 7 days offer validity from the date of closure of bid submission. Quotation received with offer validity less than 7 days from the date of closure of bid submission will be entirely rejected.


Please Submit Your Lowest Offer in a Sealed Cover Superscribing "SEALED TENDER FOR THE SUPPLY OF 20MM GREY BUTYL RUBBER STOPPERS STERILIZED - 500000 Nos. DUE ON 08.02.2024 TENDER ID:KSDP/PS/F-ST/2023-24/200000135/T-87 (ST-145)" on or before 08.02.2024, 03.00 PM to the Office of the Managing Director, Kerala State Drugs & Pharmaceuticals Ltd, Kalavoor - P.O, Alappuzha - 688522 in two cover system.

1st cover: should comprise of technical bid. Must submit COA, EMD&TC (Provide proof for exemptions of EMD & TC, if any) & other relevant documents for technical evaluation. 2nd cover: should comprise of price bid. Quotation received in any other mode or not as per the prescribed format will be rejected.

**TERMS & CONDITIONS** 

1.Payment terms :-	30 days after the receipt of the material along with documents, subject to QC approval.
2.Mode of payment:-	E-Payment.
3.Delivery Period:-	Supply should be effected within 15 days on award of PO

### **HOD - Purchase**



These are sterilized (ready to use) grey butyl non toxic rubber closures having the following specifications:

S.No	Test	Specification
1.	Description	The stopper is having four equi-distance
3- 5		lines and a small circle at the center at the
		top disc. Stoppers evenly and smoothly
		finished with uniform colour, free from
	f, and an is a di	flash and adhering rubber pieces.
2.	Colour	Grey
3.	Disc Diameter	18.60mm-19.10mm
4.	Plunger Diameter	13.00mm-13.20mm
5.	Total Height	8.20mm-8.80mm
6.	Disc Thickness	3.20mm-3.60mm
7.	Shore Hardness	40° A-50°A
8.	Fragmentation Test	Not more than 15 Fragments
9.	Self Sealability	None of the vials contains any trace of
4 1		coloured solution.
10.	Appearance of solution	Solution A is not opalescent than opalescent
		standard OS3 and not more intensely
		coloured than reference solution BYS6.
11.	Acidity or alkalinity	To 20.0ml of the solution A add 0.1ml of
		bromothymol blue solution. Not more than
		0.3ml of 0.01 M Sodium hydroxide or
		0.8ml of 0.01M Hydrochloric acid is
, 2 <sup>8</sup>		required to change the colour of the
		solution to blue or yellow respectively.
12.	pH	Not more than 0.3ml of 0.01 M Sodium
e e g		Hydroxide or 0.8ml of 0.01M Hydrochloric
		acid.

Sterilized By: Gamma Radiation

Prepared by	Checked By	Checked by	Reviewed By	Approved By
Jr. Manager QA	Dy. Manager, Production	Production Head	QC Head	QA Head
Date: 05/10/18	Date: 05/10/18	Date: 5/10/1/	Date: 5/10/18	Date: 5 10 18

MASTER COPY



# KERALA STATE DRUGS AND PHARMACEUTICALS LTD.

KALAVOOR PO, ALAPPUZHA, KERALA-688522

Specification of 20mm Grey Butyl Rubber stoppers Sterilized (Ready to use)

13.	Total Ash (%)	<u>+</u> 10%
14.	Reducing substances	Not more than 7.0ml of 0.01M Sodium
		Thiosulphate
15.	Light absorbtion	The absorbance is not more than 2.0, if
		necessary, dilute the filtrate before
т. <sup>н</sup> Ц		measurement and correct the results for the
		dilution.
16.	Volatile Sulphides	Black stain not darker than standard.
17.	Residue on evaporation	Not more than 4.0mg
18.	Heavy metals	To comply limit test.
19.	Endotoxin Content	NMT 0.25 EU/ml
20.	Sterility	No microbial Growth

# Samples to be provided for approval.

It should fit snugly with 20mm neck vials and should comply with all chemical tests specified in the IP.

\* The supplier should submit samples physically and it should pass the performance test, before sending full consignment.

Prepared by	Checked By	Checked by	Reviewed By	Approved By
Jr. Manager QA	Dy. Manager, Production	Production Head	QC Head	QA Head
Rivi	Cause	k	Spokap	Aml
Date: 05/10/18	Date: 05/10/18	Date: 510118	Date: 5/10/18	Date: 5 10 18
				UNCONTROLLED COP
	TRAN.	n i gan a la l	MAST	TER COPY

